

AUTOMATIC HEAVY DUTY COMBO SHRINK SYSTEM



MODEL: HDX250A

FEATURES

CONTROLS

- All Electric, No Air Required
- 7" Color Touchscreen
- Store Up to 128 Recipes
- Multi-level Password Protection
- Multiple Language
- Two Emergency Stop Buttons
- USB & SD Interface
- Variable Speed Conveyors

SEAL AREA

- Closing Conveyor
- 20" x 20", One Piece Blade
- Horizontal & Vertical Product Sensors
- Adjustable Seal Jaw Opening
- Adjustable Seal Pressure
- FDA Belts
- Slide On Overhead Film Cradle
- Overhead Scrap Rewind

HDX250A



TUNNEL FEATURES

- 17.75" W, 10.5" H, 37" L Chamber
- Variable Speed Roller Conveyor
- Adjustable Louvers

OTHER FEATURES

- Compact Design
- Multiple Alarms for Machine Monitoring
- Powder Coated Steel Construction
- Locking Casters
- Two Year Limited Warranty

MODEL SPECS

SEAL AREA	20"W, 20"L (508mm W, 508mm L)
TUNNEL CHAMBER	17.75" W, 10.5" H, 37" L (450.85mm W, 266.7mm H, 939.8mm L)
FILM CAPACITY	23.5" W, 11.75"OD (600mm W, 300mm OD)
PRODUCTION RATE	0 – 35 PPM, Dependent upon product and film size
MAXIMUM PRODUCT DIMENSION	15.5" W, 16.5" L, 4.5" H (400mm W, 420mm L, 120mm H)
MAXIMUM PRODUCT WEIGHT	20 LBS (9.07185 Kg)
POWER REQUIREMENTS	208-240 VAC, THREE PHASE, 22A
CONVEYOR HEIGHT	34.25" (870mm)
OVERALL DIMENSIONS	111" L, 54" W, 64" H
WEIGHT	1840Lbs. (677 Kg)

AVAILABLE OPTIONS

- 2' Gravity Exit Conveyor
- PTFE Mesh Belt Overlay for Tunnel Conveyor
- Gravity Turnaround Conveyors Available
- Infeed Conveyors
 - Flighted or Belted

